



### TECHNICAL INFORMATION

Watts:	64
Lumens:	4800LM
Shape:	Square
Input Power:	AC : 170 - 265 V , 50/60Hz
Long Life:	20,000 Hours
Unit Color:	White
Body Type:	Aluminium
PF:	>0.9
LED Chip Type:	SMD
CRI:	>70
Operation Temperature:	-20°C to +45°C
Dimmable:	No
Beam Angle:	120°
Color Temperature:	6500K
Dimension:	600x600x35mm
Lease Finish	Opal

### FEATURES

- Compare with incandescent, it can save over 80% electric cost
- Contemporary & Elegant Design
- Higher Light Transmission Rate
- Easy to install - Plug and play version
- High quality power driver ensures reliable lifetime
- Controlled Glare rating values for comfortable commercial applications
- Range of Sizes to suit different workspaces
- Instant Start - 0-100% in
- No flickering, No U.V Radiation
- No Lead or Mercury content hence Environment friendly
- Application - Office, Conference Room, Showroom, Lobby, Cabin, Kitchen etc



### TRANSFORMER / POWER SUPPLY

Model Number	32W X 2
Input	AC-170-265V - 50/60HZ
Output	600MA 48-64V

### LISTING DETAILS

### PACKAGING

Gross Weight (Kgs):	3.4
Unit CBM:	0.017914
Dimension:	600x600x35mm

### MASTER BOX PACKAGING

Box Qty:	5
----------	---